

DAMP FLOOR SOLUTION

Newton 603 flooring membrane applied as a damp treatment for moisture sensitive timber floor

History

Newton Specialist Basement Contractor Cavity Tech were contacted by the client to carry out damp proofing work on this property. During the time that the work was being carried out with subsequent re-plastering, the client mentioned that they would like a new floor. Cavity Tech suggested they could lay a secret nailed oak floor straight on top of the still damp floor by utilising Newton 603 Flooring Membrane to ensure the moisture sensitive oak would remain dry.

Methodology

Cavity Tech removed the contaminated plaster and carried out the insertion of a chemical damp proof course. Newton 603 Flooring Membrane was installed above the slab to ensure that no moisture or damp could affect the new floor.

Result

The client was able to have their home put back to a finished state quickly and without the worry about whether their expensive oak floor would be affected by moisture from the slab.

Benefits

Newton 603 Flooring Membrane is a cost effective solution as it isolated damp within the slab without the need for installing a new slab is ideal for moisture sensitive timber floors. It also allows you to put a floor with a new slab back in to use very quickly. Newton waterproofing and damp proofing membranes are quick and cost effective methods of overcoming damp and waterproofing problems in new build and refurb projects. When application is carried out by a Newton Registered Contractor, both client and major contractor have a guaranteed professional solution.

NSBC Contractor: Cavity Tech



Newton 603 installed over the original damp concrete slab



Newton 603 is the ideal product for a moisture sensitive timber floor



The damp proofed oak floor installed over Newton 603

Featured Products

NEWTON SYSTEM 600

Range of flooring membranes which provide a complete damp proof solution. Our membranes 'de-couple' the floor finish from the substrate preventing damage due to substrate movement and cracking.

Newton 601 Slimline is a high-grade flooring membrane used primarily for isolating moisture sensitive flooring from dampness in the floor slab, but can also be used as the floor membrane as part of Newton System 500 when the survey has ascertained that no risk of water entering through the body of the slab exists.

Newton recommends that our systems are installed by one of our Nationwide Network of Newton Specialist Basement Contractors (NSBC) NSBCs have been trained by Newton and can offer full professional indemnity on design and insured backed guarantees on the installation.

For a list of Newton Specialist Basement Contractors (NSBC) in your area, please e-mail info@newton-membranes.co.uk or fill out our online form: Request List of Registered Installers

Newton System 600



Newton 601 Slimline Membrane