

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

Revision: 1.0 - 15th August 2024  
Code: HC-R-25

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

- Trade name HydroCoat 1 Render

#### 1.2 Relevant identified uses

- Identified uses Professional application of coatings and inks
- Uses advised against All Other Uses

#### 1.3 Details of the supplier

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web [www.newtonwaterproofing.co.uk](http://www.newtonwaterproofing.co.uk)
- Email address of the competent person [info@newtonwaterproofing.co.uk](mailto:info@newtonwaterproofing.co.uk)
- Emergency telephone number +44 (0)1732 360 095  
9am - 5pm (GMT) Mon - Fri

### SECTION 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Dam. 1, H318

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

Causes serious eye damage.  
Causes skin irritation.  
May cause an allergic skin reaction.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### Precautionary statements

General	Not applicable.
Prevention	Wear protective gloves. Wear eye or face protection. Avoid breathing dust.
Response	IF ON SKIN: Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or physician.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	Cement, portland, chemicals Flue dust, portland cement
Supplemental label elements	Reducing agents keep soluble chromium VI levels <2ppm for a minimum period of 1 year from date of manufacture when stored in dry, unopened bags at 20°C.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification Not applicable.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Mixture

Product/ ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Type
Crystalline silica	EC: 238-878-4 CAS: 14808-60-7	≥25 - ≤50	Not classified.	-	[2]
Cement, portland, chemicals	EC: 266-043-4 CAS: 65997-15-1	≥10 - <20	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335  See Section 16 for the full text of the H statements declared above.	-	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Seek medical attention.
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Seek medical attention if irritation persists. Do NOT use solvents or thinners.
Ingestion	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact	Causes serious eye damage.
Inhalation	May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	Irritating to mouth, throat and stomach.

##### Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include the following: pain watering redness
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	Adverse symptoms may include the following: stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known.

#### 5.2. Special hazards arising from the substance or mixture

Hazards from the substance or mixture No specific fire or explosion hazard.

Hazardous thermal decomposition products Decomposition products may include the following materials: metal oxide/oxides

#### 5.3. Advice for firefighters

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

Small spill Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 7: HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1. Precautions for safe handling

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8).  
Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.  
Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.  
Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.  
Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3. Specific end use(s)

Recommendations

Not available.

Industrial sector specific solutions

Not available.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1. Control parameters

##### Occupational exposure limits

Product/ingredient name	Exposure limit values
Crystalline silica	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 0.1 mg/m <sup>3</sup> 8 hours. Form: respirable dust
Cement, portland, chemicals	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 mg/m <sup>3</sup> 8 hours. Form: inhalable dust TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable dust

#### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs** No DNELs/DMELs available.

**PNECs** No PNECs available

#### 8.2 Exposure controls

**Appropriate engineering controls** If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

##### Individual protection measures

**Hygiene measures** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### Skin protection

#### Hand protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. EN ISO 13688

#### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Solid. [powder]
Colour	Grey.
Odour	Odourless.
Odour threshold	Not available
pH	Not applicable.
Melting point/freezing point	Not applicable
Initial boiling point and boiling range	Not available
Flash point	Closed cup: 101°C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	2.67
Solubility(ies)	Soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

Viscosity	Kinematic (room temperature): 999.1 mm <sup>2</sup> /s
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information	No additional information.

### SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	No specific data.
10.5 Incompatible materials	No specific data.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

##### Acute toxicity

Conclusion/Summary : Not available.

##### Irritation/Corrosion

Conclusion/Summary : Not available.

##### Sensitisation

Conclusion/Summary : Not available.

##### Mutagenicity

Conclusion/Summary : Not available.

##### Carcinogenicity

Conclusion/Summary : Not available.

##### Reproductive toxicity

Conclusion/Summary : Not available.

##### Teratogenicity

Conclusion/Summary : Not available.

##### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Cement, portland, chemicals	Category 3	Not applicable.	Respiratory tract irritation

##### Specific target organ toxicity (repeated exposure)

Not available.

##### Aspiration hazard

Not available.



# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### Information on likely routes of exposure

Not available.

### Potential acute health effects

Eye contact	Causes serious eye damage.
Inhalation	May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following pain watering redness
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	Adverse symptoms may include the following: stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

#### Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

### Potential chronic health effects

Not available.

Conclusion/Summary	Not available.
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Other information	Not available.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Conclusion/Summary Not available.

#### 12.2 Persistence and degradability

Conclusion/Summary Not available.

#### 12.3 Bioaccumulative potential

Not available.

#### 12.4 Mobility in soil

Soil/water partition coefficient ( $K_{oc}$ ) Not available.

Mobility Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

#### 12.6 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

##### Product

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste The classification of the product may meet the criteria for a hazardous waste.

##### European waste catalogue (EWC)

Code number	Waste designation
EWC 17 01 06*	mixtures of, or separate fractions of concrete, bricks, tiles and ceramics containing hazardous substances

##### Packaging

Methods of disposal Dispose of containers contaminated by the product in accordance with local or national legal provisions. This material and its container must be disposed of as hazardous waste. Dispose of via a licensed waste disposal contractor.

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 14: TRANSPORT INFORMATION

	ADR/RID	IMDG	IATA
14.1. UN number	Not regulated.	Not regulated.	Not regulated.
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No
Additional information	-	-	-

IMDG Code Segregation group Not applicable.

14.6 Special precautions for user Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not available.

### SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV -

List of substances subject to authorisation Annex XIV

Substances of very high concern None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Other EU regulations

Europe inventory Not determined.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

National regulations

References Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)

15.2 Chemical safety assessment No Chemical Safety Assessment has been carried out.

# HydroCoat 1 Render

## Waterproof One-Coat Cementitious Render

### SECTION 16: OTHER INFORMATION

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
kin Sens. 1, H317	Calculation method

Full text of abbreviate H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Full text of classifications [CLP/GHS]

Eye Dam. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

#### Notice to reader

**IMPORTANT NOTE:** the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws. Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with Newton Waterproofing Systems.

Any specification/advice provided is only valid if used with products supplied by John Newton and Company Ltd (trading as Newton Waterproofing Systems). Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.